

Internal Breakable Joint

Creates an internal breakable joint between physical entity parts. A joint can either connect two parts, or one part to the 'ground' (connecting parts are determined automatically by checking intersections). When the entity receives impulses (from collisions or other sources), it recomputes internal forces between joints and breaks the ones that have their limits breached. Broken joints can optionally create a dynamic constraint between broken parts instead of fully disconnecting them. If the limit that broke was twist, it creates a 'hinge' (1 DOF) constraint around the joint's z axis, otherwise a bend constraint (2 DOF).

Parts that separate from the main entity are always physicalized as rigid entities (PE_RIGID).

- [Internal Breakable Joint](#)
- [Line Constraint](#)
- [Plane Constraint](#)
- [Point Constraint](#)

Property	Description																								
Internal Breakable Joint Settings	<table border="1"> <thead> <tr> <th>Setting</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Max Push Force</td> <td>Push force limit along the normal.</td> </tr> <tr> <td>Max Pull Force</td> <td>Push force limit along the normal.</td> </tr> <tr> <td>Max Shift Force</td> <td>Force limit orthogonal to the normal.</td> </tr> <tr> <td>Max Bend Torque</td> <td>Normal bend torque limit.</td> </tr> <tr> <td>Max Twist Torque</td> <td>Twist torque limit around the normal.</td> </tr> <tr> <td>DefaultDamageAccum</td> <td>Use default damage accumulation and threshold (from CVar).</td> </tr> <tr> <td>Damage Accumulation Fraction</td> <td>Accumulated fraction of damage, normalized to 0..1.</td> </tr> <tr> <td>Damage Accumulation Threshold</td> <td>Only accumulate damage if it exceeds this fraction of the maximum.</td> </tr> <tr> <td>Breakable</td> <td>Whether the joint is at all breakable.</td> </tr> <tr> <td>Direct Breaks Only</td> <td>The joint will only break if one of the parts it connects receives an impulse.</td> </tr> <tr> <td>Sensor Size</td> <td>Sensor sphere diameter for attachment and re-attachment.</td> </tr> </tbody> </table>	Setting	Description	Max Push Force	Push force limit along the normal.	Max Pull Force	Push force limit along the normal.	Max Shift Force	Force limit orthogonal to the normal.	Max Bend Torque	Normal bend torque limit.	Max Twist Torque	Twist torque limit around the normal.	DefaultDamageAccum	Use default damage accumulation and threshold (from CVar).	Damage Accumulation Fraction	Accumulated fraction of damage, normalized to 0..1.	Damage Accumulation Threshold	Only accumulate damage if it exceeds this fraction of the maximum.	Breakable	Whether the joint is at all breakable.	Direct Breaks Only	The joint will only break if one of the parts it connects receives an impulse.	Sensor Size	Sensor sphere diameter for attachment and re-attachment.
	Setting	Description																							
	Max Push Force	Push force limit along the normal.																							
	Max Pull Force	Push force limit along the normal.																							
	Max Shift Force	Force limit orthogonal to the normal.																							
	Max Bend Torque	Normal bend torque limit.																							
	Max Twist Torque	Twist torque limit around the normal.																							
	DefaultDamageAccum	Use default damage accumulation and threshold (from CVar).																							
	Damage Accumulation Fraction	Accumulated fraction of damage, normalized to 0..1.																							
	Damage Accumulation Threshold	Only accumulate damage if it exceeds this fraction of the maximum.																							
	Breakable	Whether the joint is at all breakable.																							
Direct Breaks Only	The joint will only break if one of the parts it connects receives an impulse.																								
Sensor Size	Sensor sphere diameter for attachment and re-attachment.																								
Dynamic Constraint	Properties of the constraint created after joint breaking.																								
	<table border="1"> <thead> <tr> <th>Setting</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Min Angle</td> <td>Min angle for the dynamic constraint (for bend assumed to be 0).</td> </tr> <tr> <td>Max Angle</td> <td>Max angle for the dynamic constraint.</td> </tr> <tr> <td>Force Limit</td> <td>Bend torque limit for breaking the dynamic constraint (0 mean the joint fully breaks at once)</td> </tr> <tr> <td>Ignore Collisions</td> <td>Ignore collisions between the connected parts.</td> </tr> <tr> <td>Damping</td> <td>Damping applied along the constraint's allowed degrees of freedom.</td> </tr> </tbody> </table>	Setting	Description	Min Angle	Min angle for the dynamic constraint (for bend assumed to be 0).	Max Angle	Max angle for the dynamic constraint.	Force Limit	Bend torque limit for breaking the dynamic constraint (0 mean the joint fully breaks at once)	Ignore Collisions	Ignore collisions between the connected parts.	Damping	Damping applied along the constraint's allowed degrees of freedom.												
	Setting	Description																							
	Min Angle	Min angle for the dynamic constraint (for bend assumed to be 0).																							
	Max Angle	Max angle for the dynamic constraint.																							
	Force Limit	Bend torque limit for breaking the dynamic constraint (0 mean the joint fully breaks at once)																							
Ignore Collisions	Ignore collisions between the connected parts.																								
Damping	Damping applied along the constraint's allowed degrees of freedom.																								

Line Constraint

Constrains entity movement to a line, relative to another entity. The other entity is passed to the ConstrainToEntity function, or it can be 'the world' if ConstrainToPoint is used. Rotation can optionally be fully disabled as well.

Setting	Description
Active	Whether or not the constraint should be added when the component is reset.

Lock Rotation	Whether or not the constrained object will be allowed to rotate around the axis (rotation that would steer the entity away from the axis is locked always).
Axis	Axis around which the physical entity is constrained. If one of these axes is already set to a positive value and you change a different one, the difference will be split between both axes. This allows you to create more complex movement along multiple axes at the same time.
Minimum Limit	Distance limit along the axis. Twist rotation limit (in angles) for splines. A unit of -1 indicates that the minimum position is one meter behind the entity.
Maximum Limit	Distance limit along the axis. Twist rotation limit (in angles) for splines. A unit of +1 indicates that the maximum position is one meter ahead of the entity.
Damping	Determines how much the object loses momentum (as it moves) while the constraint is active.
Attachment Parameters	
No Attachment Collisions	If the Constraint is attached to another entity (either via Target Link Name or Auto Attachment Distance, see below), automatically disable collisions with it.
Auto Attachment Distance	When >0, will sample physical environment within this distance to find an entity to attach to. Any physical constraint constrains 2 entities. the first one is always the one that owns the component. the other one can be auto-detected.
Target Link Name	Name of the entity link that contains the entity to attach to.
Helper Link Name	Name of the entity link that contains the 'constraint helper' entity, such a physical area with a surface or a spline. Target Link Name and Helper Link Name are needed to give the component a reference to another entity, for example you create an entity link with a certain name, and specify that link name as the Target Link Name.

Plane Constraint

Constrains entity movement to a plane, relative to another entity. The other entity is passed to ConstrainToEntity function, or it can be 'the world' if ConstrainToPoint is used. Rotation can optionally be limited as well.

Setting	Description
Active	Whether or not the constraint should be added on component reset.
Axis	The normal of the plane the entity will be constrained to (in the component's frame).
Twist rotation min angle	Rotation limits minimum around x axis. (If this value is bigger than the max value the x axis will be locked)
Twist rotation max angle	Rotation limits maximum around x axis.
Bend max angle	Maximum bend angle of the rotation.
Damping	Determines how much the object loses momentum (as it moves) while the constraint is active.
Attachment Parameters	
No Attachment Collisions	If the Constraint is attached to another entity (either via Target Link Name or Auto Attachment Distance, see below), automatically disable collisions with it.

Auto Attachment Distance	When >0, will sample physical environment within this distance to find an entity to attach to. Any physical constraint constrains 2 entities. the first one is always the one that owns the component. the other one can be auto-detected.
Target Link Name	Name of the entity link that contains the entity to attach to.
Helper Link Name	Name of the entity link that contains the 'constraint helper' entity, such a physical area with a surface or a spline. Target Link Name and Helper Link Name are needed to give the component a reference to another entity, for example you create an entity link with a certain name, and specify that link name as the Target Link Name.

Point Constraint

Creates a point-to-point constraint between 2 entities. The other entity is passed to ConstrainToEntity function, or it can be 'the world' if ConstrainToPoint is used. Rotation can be constrained in two dimensions: as rotation around the constraint axis and as bending of that axis on one entity's frame relative to it the other entity's frame.

Setting	Description
Active	Whether or not the constraint should be added when the component is reset.
Axis	Axis around which the physical entity is constrained.
Free Position	Constrains the rotation, leaving the position free.
Minimum X Angle	Minimum angle for rotation around the axis ('twisting')
Maximum X Angle	Maximum angle for rotation around the axis ('twisting')
Maximum YZ Angle	Maximum angle for bending of the axis.
Damping	Determines how much the object loses momentum (as it moves) while the constraint is active. Values of 0.1 to 0.4 are very common and realistic.
Attachment Parameters	
No Attachment Collisions	If the Constraint is attached to another entity (either via Target Link Name or Auto Attachment Distance, see below), automatically disable collisions with it.
Auto Attachment Distance	When >0, will sample physical environment within this distance to find an entity to attach to. Any physical constraint constrains 2 entities. the first one is always the one that owns the component. the other one can be auto-detected.
Target Link Name	Name of the entity link that contains the entity to attach to.
Helper Link Name	Name of the entity link that contains the 'constraint helper' entity, such a physical area with a surface or a spline. Target Link Name and Helper Link Name are needed to give the component a reference to another entity, for example you create an entity link with a certain name, and specify that link name as the Target Link Name.